

# KISS 1U Short V3 CFL

---



## Scalable Rackmount System for challenging and noise sensitive environments

- ▶ Industrial grade for challenging environments – robust, reliable and sustainable
- ▶ High processing capability with 8th/9th Gen Intel® Core™ i7/i5/i3
- ▶ Modular concept allows easy customization
- ▶ Low noise level

POSSIBILITIES START HERE



# KISS 1U Short V3 CFL

Kontron's KISS rackmount systems are designed and tested for challenging environments, and are therefore the perfect fit for high temperature and mechanical stress conditions. Industrial grade design, in combination with high processing performance allows industrial applications requiring high performance and storage capabilities, e.g. high-end image processing and SCADA/MES applications. The new KISS rackmount systems are ideally suited even for complex computing tasks such as 'Artificial Intelligence'

(AI) and machine learning based on processing and analytics of a huge amount of data. Efficient thermal concepts, maintenance-free and customizable designs, high performance computing and graphics power enable 24/7 operation and long-term deployment. A high degree of customization is facilitated through features like removable drives and various expansion cards.

## ▶ TECHNICAL INFORMATION

<b>SYSTEM</b>	KISS 1U Short V3 CFL
<b>DIMENSION</b>	44 x 482 x 350 mm (1U x 19" x 13.78")
<b>WEIGHT</b>	Approx. 6 kg
<b>PROCESSOR</b>	8th/9th Gen Intel® Core™ i7/i5/i3 series
<b>CHIPSET</b>	Intel® C246 Express Chipset
<b>RAM</b>	4x DIMM DDR4-2666 up to 64 GByte
<b>FRONT I/Os</b>	2x USB 2.0, optional 2x USB 3.0
<b>REAR I/Os</b>	4x USB 3.1, 4x USB 2.0, 2x GB LAN, 1x DVI-D, 2x DP 1x RS232, 1x Mouse, 1x Kbd, 1x Audio
<b>DRIVE OPTIONS</b>	1x DVD R/W slim 1x 3.5" SATA drive bay 1x M.2 2280 PCIe drive RAID support
<b>POWER SUPPLY</b>	100-240 V AC 400 W (80+)
<b>EXPANSION SLOTS</b>	1 Slot PCIe x16 (Low Profile)
<b>EXPANSION CARDS</b>	2x GByte LAN, 2x 10 GByte LAN, others on request
<b>CERTIFICATIONS</b>	CE, FCC, NRTL (UL 62368-1), CB (IEC 62368-1)
<b>ALTITUDE</b>	5000 m operating
<b>SHOCK* ACCORDING TO EN 60068-2-27</b>	Operating: 15 G 11 ms duration Non-operating: 30 G 11 ms duration
<b>VIBRATION ACCORDING TO EN 60068-2-6</b>	Operating: 10-150 Hz: 1G/3 axis Non-operating: 10-150 Hz: 2G/3 axis
<b>OPERATING TEMPERATURE</b>	0 °C to +50 °C continuous operation
<b>STORAGE TEMPERATURE</b>	-20 °C to +70 °C
<b>HUMIDITY</b>	10 % to 93 % @40 °C, non-condensing
<b>MTBF</b>	> 50.000 h
<b>VERIFIED OS</b>	Windows 10 64 bit LTSC Linux others on request

\*) no HDD

## ▶ GLOBAL HEADQUARTERS

### Kontron Europe GmbH

Gutenbergstraße 2  
85737 Ismaning, Germany  
Tel.: +49 821 4086-0  
Fax: +49 821 4086-111  
info@kontron.com

[www.kontron.com](http://www.kontron.com)